



Specifications:

Fabric Use	Road Stabilization	Filter	Silt Fence
Fabric Type	Woven	Non-Woven	Woven
Inventory #	SF-GS	FF-3x400 or FF-12.5x400	Silt
Manufacturer #	200W	480HS	M150
Width (ft)	12.5'	3' or 12.5'	3'
Length (ft)	400'	400'	100'
Weight (oz/yd)	4.2	4.0	na
Thickness D-1777	na	60 mils	na
Grab Str D-4632-86	200 lbs	120 lbs	90 lbs
Elongation D-4632-86	20%	75%	15%
Puncture D-4833	90 lbs	45 lbs	60 lbs
Burst Str D-3786-85	400 psi	215 psi	325 lbs
Tear Str. D-4533-85	90 lbs	50 lbs	75 lbs
AOS D-4751	40	70-140	50
Water Flow D-4491	na	170	40
Permitivity D-4491	0.125	1.7	na
UV Resistance D-4355-84	70%	85%	80%

SPECIFICATIONS	
See Chart on Right	GEOTEXTILES
	<p>Woodard's Concrete Products, Inc. 629 Lybolt Road, Bullville, NY 10915 (845) 361-3471 / Fax 361-1050</p> <p>Page 5H 7/13/06</p>